Elastomeric Emulsion

TULSICRYL EE-50



TULSICRYL EE-50 - ELASTOMERIC EMULSION is a pure acrylic emulsion for high-performance Elastomeric Coatings. It has a very high filler binding power. Film forms have excellent water resistance & have very good dirt pick-up resistance. Elastomeric coating manufactures elastic coatings such as elastic top and midcoats. The product has special properties that are required for a successful elastomeric coating.

PRODUCT SPECIFICATIONS

Chemical Name	PURE ACRYLIC COPOLYMER EMULSION
Appearance	Bluish milky white emulsion
Solid content, weight %	50 ± 1%
рН	8 - 10
Brookfield viscosity	2 – 20 Ps, SP#2, 20 RPM @ 30°C
MFFT (°C)	5 ± 1
Mechanical stability	Good
Density	1.02 ± 0.02 gm/ml
Film	Clear
Surface	Non-tacky

FILM PROPERTIES

High elastomeric, wet scrub-resistant, waterproof, durable exterior film with excellent dirt pick-up resistance, wet adhesion, and water resistance.

APPLICATIONS

Recommended for roof coatings, elastomeric exterior wall coatings, waterproofing, anti-carbonation, and damp-proof coatings.

STORAGE AND HANDLING

TULSICRYL EE-50 has a shelf life of 12 months from the date of manufacture, provided it is stored under shade, away from direct heat and sunlight, and well protected from freezing.

PACKING

Flexi tanks, 240/250 kg HDPE Drums.

NOTE: The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other company's raw materials are also being used. The recommendations do not absolve the user from the obligation of investigation of the possibility of infringement of third parties rights and, if necessary, clarifying the positions.